


HP 1.25 LEVEL 2 ACRYLIC





Innovative glazing solutions for ballistic protection

PRODUCT DESCRIPTION

HP 1.25 ACRYLIC HAS BEEN TESTED AND CERTIFIED TO MEET UL 752 LEVEL 2 BALLISTICS PERFORMANCE

TECHNICAL DATA

- Nominal Thickness: 1.378"
- Weight: 8.5 lbs per SF
- Light Transmittance: >90%
- Haze: <1.0%
- Yellowness Index: < 0.7%
- Abrasion Resistance (coated): .2 to 2.0 (% haze change)
- Tensile Strength: 9,500psi
- Tensile Modulus: 400,000psi
- Flex Modulus: 400,000psi
- Burn Rate: .1.2in/min
- Smoke Density: Max 8%: Rating 5%
- · Auto Ignition Temp: 465°C, 870°F

PERFORMANCE

- .357 magnum
- UL 752 Level 2
- No Spall, No Penetration

OPTIONS:

- Polycast SAR Super Abrasion-Resistant Coating
- Standard Tints
- Sheet sizes up to 6' x 10'

CODE RATINGS AND STANDARDS

- · Meets the test requirements of Building Code class CC2
- ANS, Z97.1 Safety Glazing Material
- ANS, Z26.1 Motor Vehicle Safety
- Glazing Material
- Dade County Approval, Federal
- Specification L-P-391D+ASTM D 4802

Maximum Continuous Service Temperature:

170° F

Minimum Continuous Service Temperature:

-26° F (lowest temperature tested for bullet resistance)

